



Nolek C9 Instrument



C9 Calibration Instrument

Is used for accurate calibration and adjustment of airflow from adjustable control leak in our instruments for dense or flow control. The C9 can be used with instruments intended for both over and under pressure. The

C9 is easy to handle because the flow value is obtained directly in (mm³/s) or (cm³/min) on the display.

There are two different models of the C9: C9 L (Measurement range 4-500mm³ / s) or C9 H (Measurement range 100-9999mm³ / s).

FUNCTIONS

- Automatic shut off
- log of measuring values
- PC comunication
- Robust design
- Easy to use
- Lighted display

TECHNICAL DATA

Pressure range:	0-1 bar
Reaction time:	20 ms
Measure range C9 L:	4-500 mm ³ /s 0,25-30 cm ³ /min
Measure range C9 H:	100-9999 mm ³ /s 6-600 cm ³ /min
Measure tolerance:	< ± 0.15% FS + ±1% RD



IN THE PACKAGE

C9 Calibration instrument	1 st
Length: 170 mm	
wigth: 80 mm	
High: 35 mm	
Weight: 390 g	
Batery (AA)	2 st
Calibrateing tube S9	1 st
Calibrateing tube DeFlux	1 st
Operators manual	1 st
Protective case	1 st
Certificat of calibration according to DKD (Deutscher Kalibrier-dienst)	1st

ACCESSORIS

- C9 Battery eliminator 5V DC, cable included.

