



- Leak Testing -

TRACER GAS CHARGING

ChargeIT

"The best way of tracer gas filling"



Nolek ChargeIT

ChargeIT is a multifunctional system with a user friendly touch screen interface that allows for easy selection and configuration of the various unique functions shown below. The ChargeIT unit is the first one of its kind and solves problems that many customers have today with leak detection. The pioneer Nolek technology started a new era in leak detection technology. Functions are:

- ⇒ Proof Test (Option)
- ⇒ Pressure Decay (Option)
- ⇒ Evacuation (vacuum pump option)
- ⇒ Vacuum Decay
- ⇒ Helium Charging
- ⇒ Cleaning and Back Fill

Specifications

Pressure range	0 – 10 bar
Signal presentation	Screen; green, yellow and red indication
Dimensions HxWxD	250x140x240 mm (9,8x5,5x9,5 Inch)
Connections	Test object, compressed air, tracer gas 8 mm tubing
Weight	5,9 Kg
Pilot air	5 – 9 bar
Operating Temperature	10-40 °C
Storage temperature	-10°C to 60 °C
Supply Voltage	Single phase 85-260VAC
Standard included	Power cord and connection kit
Options	Venturi Pump Kit, Helium regulator

www.nolek.com

Visit Today for your enquiry or specific need!



- Leak Testing -

